EMDEK 1500 Forage Chopper



The Emdek 1500 forage chopper is suitable for tractors of 60-80 Hp fitted with a Cat 2 three point linkage and 540 rpm power take-off shaft with 6 splines.

Tractor should have position control. Able to chop forage and convey/blow the chopped material to a container/trailer at the rear. Can be modified to cut and clean grasses in airport areas.

EMDEK SDN BHD

Lot 10220, Jalan Lombong Emas 5 Seremban Light Industrial Park 70200 Seremban, N Sembilan Malaysia

Tel: 06-7641320/764216

Fax: 06-7641310

E-mail: sales@emdek.com.my



tandard Equipment:

Cable chute controls (Standard supply) for swivel of discharge chute controlled from tractor seat.

P.T.O. Shaft with friction clutch



21 pcs. Rotary Chopping knives



Standard and optional counter knives

Technical specifications:

Cutting width

Number of flails

Tyre size

Wheel base

PTO power requirement min.

Transmission

4 V-belts

P.T.O.

1500mm

21 pcs
6,00-12"

adjustable

60 HP

4 V-belts

540 rpm

Rotor r.p.m. with

260 mm dia. Pulley 1670 rpm

220 mm dia, Pulley 1430 rpm (Optional) 180 mm dia. Pulley 1180 rpm (Optional)

Height with discharge chute 3500 mm

Height without discharge chute 2500 mm

Total width without linkage 1940 mm
Total length 3370 mm
Total weight 635 kg

80 hp rated gearbox built-in with overrun free wheeling clutch system.

Standard one set blade adjustable counter chopping knife for chopping grass.

Optional extra set of counter chopping knife for chopping beet root and other fodder.