

EMDEK EMD15 CANNON AIR BLAST SPRAYER





EMDEK CANNON AIR BLAST SPRAYER

Developed and built in Malaysia for use in tall oil palm areas specially for bag worms and other pest and diseases. Suitable for use mounted on three point linkages of tractors with a minimum of 60HP and 540rpm PTO.

Specifications:

- * Models with 600 or 800 litres capacity fiberglass tanks mounted onto tubular steel frames.
- * Cat 1 and 2 three point linkage.
- * Fiberglass tanks fitted with strainer basket with a polyethylene cover with breather, drain plug, level indicator panel, return flow connector.
- * Annovi Reveberi model 503 high pressure diaphragm pump with max. 45 lit/min @ 40 bar pressure at 500 rpm rotation.
- * Annovi Reveberi VDR50 pressure control with 4 outlets, on/off main switch and a glycerine filled pressure gauge. Pressure is adjustable with a pressure control knob.
- * Oil lubricated step-up gearbox with 1:3.5/Neutral/1:4.5 ratios
- * High speed turbine fan driven by a 2 speed gearbox capable of reaching a max speed of 2,430 rpm that gives air volume of 30,000 cu m per hour
- * Air blast direction is adjustable 90° angles manually
- * Twin spray heads, each with 4 brass spray nozzles fitted with ceramic spray jets of different sizes available as options. Housing is made of fiberglass.
- * Max. vertical height of spray 15-20M under no-wind conditions depending on the number of spouts selected.
- * Available options: Single spout and double spouts.
- * Pressure agitation of chemicals in the tank with ejector nozzles.

EMDEK SENDIRIAN BERHAD

Lot 10220, Jalan Lombong Emas 5
Seremban Light Industrial Park

Tel: +60 6 7641320/7641216
Fax: +60 6 7641310

70200 Seremban
N Sembilan, Malaysia

Emails : emdek2009@gmail.com / sales@emdek.com.my
Website: www.emdek.com.my