

EMDEK TURBO-SPIN 650/850 TRACTOR MOUNTED FERTILIZER SPREADERS



The EMDEK TURBO-SPIN fertilizer spreader is patented for use to spread dry fertilizers with a greater throw distance covering a wider area evenly without dropping fertilizers on the tractor path. Specially designed for use in tree crops in row plantings. Available in 650 and 850 kg capacities. Fitted with deflectors, the fertilizers can be directed to give an accurate throw. Specially designed grease lubricated gearbox for minimal trouble-free maintenance.

Suitable for tractors of 55-80Hp with 540 rpm PTO.

3 Versions available in enamel paint, Galvanized frame and full stainless steel frames and gearbox housing.

Model	Hopper Capacity	Frame Construction	Tractor linkage Category	Tractor HP * Required	Spreading Total Width** on both sides	Weight (Empty)
TURBO-SPIN 650	650 kg	MS Primed & enamel paint top coat	Cat 1 & 2	55-70	5 -25 m	235 kg
TURBO-SPIN 650G	650 kg	Zinc Galvanized	Cat 1 & 2	55-70	5-25 m	250 kg
TURBO-SPIN 650SS	650 kg	Stainless Steel	Cat 1 & 2	55-70	5-25 m	239 kg
TURBO-SPIN 850	850 kg	MS Primed & Enamel paint top coat	Cat 1 & 2	60-80	5-25 m	243 kg
TURBO-SPIN 850G	850 kg	Zinc Galvanized	Cat 1 & 2	60-80	5-25 m	258 kg
TURBO-SPIN 850SS	850 kg	Stainless Steel	Cat 1 & 2	60-80	5-25 m	247 kg

* Tractor used must have max. 540 rpm P.T.O.

**Depending on quality and type of fertilizers used – based on granular fertilizers

EMDEK SENDIRIAN BERHAD

Lot 10220, Jalan Lombong Emas 5
Seremban Light Industrial Park
70200 Seremban, N Sembilan
Malaysia

Tel: +60 6 7641320/7641216

Fax: +60 6 7641310

Emails: emdek2009@gmail.com / sales@emdek.com.my

Website: <http://www.emdek.com.my>

EMDEK TURBO MINI 300/500 TRACTOR MOUNTED FERTILIZER SPREADERS



Turbo Mini 300G

Turbo Mini 500G

The EMDEK TURBOMINI fertilizer spreader is patented for use to spread dry fertilizers with a greater throw distance covering a wider area evenly without dropping fertilizers on the tractor path. Specially designed for use in tree crops in row plantings. Available in 300 and 500 kg capacities. Fitted with deflectors, the fertilizers can be directed to give an accurate throw. Specially designed grease lubricated gearbox for minimal trouble-free maintenance. Suitable for tractors of 25-40 Hp with 540 rpm PTO.

Model	Hopper Capacity	Frame Construction	Tractor linkage Category	Tractor HP * Required	Spreading Total Width** on both sides	Weight (Empty)
TURBO-Mini300	300 kg	MS Primed & Enamel paint top coat	Cat 1	25-45	5-15 m	144 kg
TURBO-Mini300G	300 kg	Zinc Galvanized	Cat 1	25-45	5-15 m	152 kg
TURBO-Mini300SS	300 kg	Stainless steel	Cat 1	25-45	5-15 m	146 kg
TURBO-MINI500	500 kg	MS Primed & Enamel paint top coat	Cat 1	30-55	5-15 m	151 kg
TURBO-MINI500G	500 kg	Zinc Galvanized	Cat 1	30-55	5-15 m	159 kg
TURBO-MINI500SS	500 kg	Stainless Steel	Cat 1	30-55	5-15 m	153 kg

* Tractor used must have max. 540 rpm P.T.O.

** Depending on quality and type of fertilizers used – based on granular fertilizers

EMDEK SENDIRIAN BERHAD

Lot 10220, Jalan Lombong Emas 5
Seremban Light Industrial Park
70200 Seremban, N Sembilan
Malaysia

Tel: +60 6 7641320/7641216

Fax: +60 6 7641310

Emails: emdek2009@gmail.com / sales@emdek.com.my

Website: <http://www.emdek.com.my>